




Trade name

# ISOBUTYL ACETATE

**Chemical Name** ISOBUTYLACETATE

**Chemical Structure** CH<sub>3</sub>COOCH<sub>2</sub>CH(CH<sub>3</sub>)<sub>2</sub>



**Molecular Formula** C<sub>6</sub>H<sub>12</sub>O<sub>2</sub>

**Molecular Weight** 116.2

**CAS No.** 110-19-0

**EINECS No.** 203-745-1

**TSCA** On Inventory

Specification	Item	Unit	Specification	Method
	Appearance		Clear Liquid	
	Color	APHA	10 max.	JIS K 0071
	Specific Gravity	20/20°C	0.871 - 0.875	JIS K 0061
	Purity	Wt %	98.0 min.	JIS K 0114
	Water Content	Wt %	0.10 max.	JIS K 0068
	Distillation test	I.B.P.	113°C min.	JIS K 0066
		D.R. (113-119°C)	97 ml min.	JIS K 0066
		D.P.	119°C max.	JIS K 0066
	Nonvolatile Matter	g/100ml	0.002 max.	JIS K 0067
	Acid Value	KOHmg/g	0.05 max.	JIS K 0070

Physical Property	Item	Unit	
	Boiling Point	°C	116.6
	Specific Gravity (20/20°C)	°C	0.873
	Melting Point	°C	-98.9
	Refractive Index	n <sub>D</sub> <sup>20</sup>	1.388
	Viscosity (20°C)	mPa·s	0.7
	Flash Point(closed cup)	°C	21.5
	Vapor Density (Air=1)	°C	4.0
	Explosion Limits	Vol%	2.4 – 10.5
	Ignition Point	°C	423
	Solubility (in Water 20°C)	g/100g	0.63
	Specific Heat(20°C)	J/mol·K	223

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Kyowa Hakko Chemical Co., LTD. It relates only to the specific material designated herein, and does not relate to use in combination with any other material or any process. Kyowa Hakko Chemical Co., LTD. assumes no legal responsibility for use of or reliance upon this information.

<b>Health Hazards</b>	Acute toxicity data on ISOBUTYLACETATE			
	Acute Toxicity	LD50(oral)	rat	15.4g/Kg
<b>Emergency and First Aid Procedure</b>	1)Skin Contact	Remove contaminated clothing. Wash the affected area with plenty of clean water and soap. If irritation develops, see a physician.		
	2)Eye Contact	Flash eyes with plenty of clean water for at least 15 minutes while holding eyelids open. If irritation develops, see a physician.		
	3)Inhalation	If a large amount is inhaled, remove individual(s) to fresh air.		
<b>Storage</b>	Tighten the cap of container and store in a cool, dry, well-ventilated, storage area of cabinet.			
<b>Extinguishing Media</b>	Water spray, Dry chemicals, Protein type air foams or carbon dioxide.			
<b>Packing</b>	180Kg	Iron drum		
	20MT	ISO-Container		

**Kyowa Hakko Chemical Co.,Ltd.**

3-2-15 Nihonbashi-Muromachi,  
Chuo-ku, Tokyo, 103-0022, Japan  
Tel: +81-3-3510-3552  
Fax: +81-3-3510-3571

**Kyowa Hakko USA, Inc**

767 Third Avenue, 19th Fl.  
New York, NY 10017, USA  
Tel: +1-212-319-5353  
Fax: +1-212-421-1283

**Kyowa Hakko Europe GmbH**

Immermannstr. 3  
D-40210 Dusseldorf  
Germany  
Tel: +49-211-17-728-0  
Fax: +49-211-17-728-41

**Kyowa Hakko Industry (Singapore) Pte. Ltd.**

260 Orchard Road #12-04  
The Heeren, Singapore 238855  
Tel: +65-6733-4948  
Fax: +65-6733-0819

**Kyowa Hakko Chemical Co.,Ltd.**

Shanghai Representative Office  
8 Xingyi Road MaxDo Bldg., Room  
908, Changning District, Shanghai  
200336, China  
Tel: +86-21-5208-0009  
Fax: +86-21-5208-0130

**Home page**

[www.kyowachemical.co.jp](http://www.kyowachemical.co.jp)

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Kyowa Hakko Chemical Co., LTD. It relates only to the specific material designated herein, and does not relate to use in combination with any other material or any process. Kyowa Hakko Chemical Co., LTD. assumes no legal responsibility for use of or reliance upon this information.